



## 1. Product and company identification

<b>Product name</b>	Castrol GTX High Mileage 20W-50
<b>MSDS #</b>	460921
<b>Code</b>	460921-US12;US13
<b>Product use</b>	Engine oils. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
<b>Manufacturer</b>	BP Lubricants USA Inc. 1500 Valley Road Wayne, NJ 07470 Telephone: (973) 633-2200 Telecopier: (973) 633-7475
<b>EMERGENCY HEALTH INFORMATION:</b>	1 (800) 447-8735  Outside the US: +1 703-527-3887 (CHEMTREC)
<b>EMERGENCY SPILL INFORMATION:</b>	1 (800) 424-9300 CHEMTREC (USA)
<b>OTHER PRODUCT INFORMATION</b>	1 (866) 4 BP - MSDS (866-427-6737 Toll Free - North America) email: bpcares@bp.com

## 2. Hazards identification

<b>Physical state</b>	Liquid.
<b>Color</b>	Not available.
<b>Emergency overview</b>	WARNING!  CAUSES RESPIRATORY TRACT AND EYE IRRITATION. MAY CAUSE SKIN IRRITATION.  Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
<b>Routes of entry</b>	Dermal contact. Eye contact. Inhalation. Ingestion.
<b>Potential health effects</b>	
<b>Eyes</b>	Causes eye irritation.
<b>Skin</b>	May cause skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
<b>Inhalation</b>	Causes respiratory tract irritation.
<b>Ingestion</b>	Ingestion may cause gastrointestinal irritation and diarrhea.

See toxicological information (section 11)

### 3. Composition/information on ingredients

Ingredient name	CAS #	%
Base oil - highly refined	Mixture	95 - 100
Zinc alkyl dithiophosphate	68649-42-3	1 - 5

### 4. First aid measures

<b>Eye contact</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
<b>Skin contact</b>	Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.
<b>Inhalation</b>	If inhaled, remove to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Get medical attention.
<b>Ingestion</b>	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately. Get medical attention if symptoms occur.

### 5. Fire-fighting measures

<b>Flash point</b>	Open cup: >200°C (>392°F)
<b>Fire/explosion hazards</b>	In a fire or if heated, a pressure increase will occur and the container may burst.
<b>Extinguishing media</b>	
<b>Suitable</b>	Use an extinguishing agent suitable for the surrounding fire.
<b>Not suitable</b>	Do not use water jet.
<b>Fire-fighting procedures</b>	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
<b>Hazardous combustion products</b>	Combustion products may include the following: phosphorus oxides metal oxide/oxides carbon oxides (CO, CO <sub>2</sub> ) (carbon monoxide, carbon dioxide) sulfur oxides (SO <sub>2</sub> , SO <sub>3</sub> etc.) nitrogen oxides (NO, NO <sub>2</sub> etc.)
<b>Protective clothing (fire)</b>	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### 6. Accidental release measures

<b>Personal precautions</b>	No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
<b>Environmental precautions</b>	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
<b>Methods for cleaning up</b>	
<b>Large spill</b>	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

<b>Product name</b> Castrol GTX High Mileage 20W-50	<b>Product code</b> 460921-US12;US13	<b>Page:</b> 2/6
<b>Version</b> 1	<b>Date of issue</b> 01/14/2008.	<b>Format</b> US
	<b>Build</b> 6.4.1 (US)	<b>Language</b> ENGLISH. (ENGLISH)

### Small spill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## 7. Handling and storage

### Handling

Put on appropriate personal protective equipment (see section 8). Workers should wash hands and face before eating, drinking and smoking. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

### Storage

Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### Other information

Sulfur compounds in this material may decompose when heated to release hydrogen sulfide gas which may accumulate to potentially lethal concentrations in enclosed air spaces. Vapor concentrations of hydrogen sulfide above 50 ppm, or prolonged exposure at lower concentrations, may saturate human odor perceptions so that the smell of gas may not be apparent. Exposure to concentrations of hydrogen sulfide vapor above 500 ppm may cause rapid death. Do not rely on the sense of smell to detect hydrogen sulfide.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### Ingredient name

Base oil - highly refined

#### Occupational exposure limits

##### ACGIH (United States).

STEL: 10 mg/m<sup>3</sup> 15 minute(s). Form: Oil mist, mineral

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral

##### OSHA (United States).

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

### Some states may enforce more stringent exposure limits.

### Control Measures

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

### Personal protection

#### Eyes

Avoid contact with eyes. Safety glasses with side shields or chemical goggles.

#### Skin and body

Do not get on skin or clothing. Wear suitable protective clothing.

#### Respiratory

Use adequate ventilation. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable.

#### Hands

The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Consult your supervisor or S.O.P. for special handling instructions.

**Product name** Castrol GTX High Mileage 20W-50

**Product code** 460921-US12;US13 **Page:** 3/6

**Version** 1 **Date of issue** 01/14/2008.

**Format** US

**Language** ENGLISH.

Build 6.4.1 (US)

(ENGLISH)

---

## 9. Physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Flash point</b>	Open cup: >200°C (>392°F)
<b>Specific gravity</b>	0.876 to 0.888
<b>Viscosity</b>	Kinematic: 19.7 to 21 mm <sup>2</sup> /s (19.7 to 21 cSt) at 100°C
<b>Solubility</b>	Insoluble in water.

---

## 10. Stability and reactivity

<b>Stability and reactivity</b>	The product is stable.
<b>Conditions to avoid</b>	Keep away from heat, sparks and flame.
<b>Incompatibility with various substances</b>	Reactive or incompatible with the following materials: oxidizing materials.
<b>Hazardous decomposition products</b>	Hydrogen Sulfide (H <sub>2</sub> S)
<b>Hazardous polymerization</b>	Hazardous polymerization may occur under certain conditions of storage or use.

---

## 11. Toxicological information

<b>Other information</b>	USED ENGINE OILS Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
<b>Potential chronic health effects</b>	
<b>Carcinogenicity</b>	No known significant effects or critical hazards.

---

## 12. Ecological information

No testing has been performed by the manufacturer.

---

## 13. Disposal considerations

<b>Waste information</b>	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
--------------------------	---

**NOTE: The generator of waste has the responsibility for proper waste identification (based on characteristic(s) or listing), transportation and disposal**

---

## 14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

<b>Product name</b> Castrol GTX High Mileage 20W-50	<b>Product code</b> 460921-US12;US13	<b>Page:</b> 4/6	
<b>Version</b> 1	<b>Date of issue</b> 01/14/2008.	<b>Format</b> US	<b>Language</b> ENGLISH.
		Build 6.4.1 (US)	(ENGLISH)

## 15. Regulatory information

### U.S. Federal regulations

**United States inventory (TSCA 8b):** All components are listed or exempted.

TSCA 12(b) one-time export: Diphenylamine

TSCA 12(b) annual export notification: Alkylated phenol (P-00-346); lead

**SARA 302/304/311/312 extremely hazardous substances:** No products were found.

**SARA 302/304 emergency planning and notification:** No products were found.

**SARA 302/304/311/312 hazardous chemicals:** No products were found.

**SARA 311/312 MSDS distribution - chemical inventory - hazard identification:** Castrol GTX High Mileage 20W-50: Immediate (acute) health hazard

### SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	Zinc alkyl dithiophosphate		0 - 1.68
Supplier notification	Zinc alkyl dithiophosphate		0 - 1.68
CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4):	CERCLA: Hazardous substances.: Arsenic: 1 lb. (0.454 kg); Cadmium: 10 lbs. (4.54 kg); lead: 10 lbs. (4.54 kg); phosphorodithioc acid, O,O - di- C1-14- alkyl esters zinc salts ; Zinc alkyl dithiophosphate: 1 lb. (0.454 kg); Ethylene glycol; ethanediol: 5000 lbs. (2270 kg);		

### State regulations

#### Massachusetts Substances

**Massachusetts Substances:** The following components are listed: MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED LIGHT PARAFFINIC

#### New Jersey Hazardous Substances

**New Jersey Hazardous Substances:** The following components are listed: Zinc alkyl dithiophosphate

#### Pennsylvania RTK Hazardous Substances

**Pennsylvania RTK Hazardous Substances:** The following components are listed: Zinc alkyl dithiophosphate

#### California Prop. 65

**WARNING:** This product contains a chemical known to the State of California to cause cancer. Paraffin oils, ; Arsenic

**WARNING:** This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. Cadmium; lead

### Inventories

**Canada inventory:** All components are listed or exempted.

**Europe inventory:** At least one component is not listed in EINECS but all such components are listed in ELINCS.

Please contact your supplier for information on the inventory status of this material.

**Australia inventory (AICS):** All components are listed or exempted.

**China inventory (IECSC):** All components are listed or exempted.

**Japan inventory (ENCS):** At least one component is not listed.

**Korea inventory (KECI):** All components are listed or exempted.

**Philippines inventory (PICCS):** At least one component is not listed.

## 16. Other information

### Label requirements

WARNING!

CAUSES RESPIRATORY TRACT AND EYE IRRITATION.  
MAY CAUSE SKIN IRRITATION.

### HMIS® Rating :

Health 1  
Flammability 1  
Physical Hazard 0

National Fire Protection Association (U.S.A.)

Health 1  
Fire hazard 1  
Instability 0  
Specific hazard 0

Product name Castrol GTX High Mileage 20W-50

Product code 460921-US12;US13 Page: 5/6

Version 1 Date of issue 01/14/2008.

Format US

Language ENGLISH.

Build 6.4.1 (US)

(ENGLISH)

**Personal protection** X

**History**

**Date of issue** 01/14/2008.  
**Date of previous issue** No previous validation.  
**Prepared by** Product Stewardship

**Notice to reader**

*NOTICE : This Material Safety Data Sheet is based upon data considered to be accurate at the time of its preparation. Despite our efforts, it may not be up to date or applicable to the circumstances of any particular case. We are not responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices or from hazards inherent in the nature of the product.*