



Visco 7000

Applications

BP Visco 7000 0W-40 with Cleanguard Engine Protection Technology is a Super Premium fully synthetic engine oil suitable for use in automotive gasoline and diesel engines including turbo charged and intercooled where the manufacturer recommends API SM/CF, ACEA A3/B3, A3/B4, C2,C3 or earlier specifications. Visco 7000 0W-40 is also approved for use in BMW, Porsche, VW and Mercedes cars including those equipped with a diesel particulate filter.

Main Benefits

BP Visco with Cleanguard Engine Technology keeps your engine cleaner for longer.

BP Visco 7000 0W-40 is a Super Premium fully synthetic engine oil that provides:

- Ultimate engine cleanliness
 - Outstanding protection against extreme conditions
 - Prolongs the life of modern emissions systems
 - Reduced harmful emissions
 - Improved fuel economy
-

Specifications

API SM/CF
ACEA A3/B3, A3/B4, C2, C3

BMW Longlife-04 (do not use in gasoline engines outside the EU)
VW 502 00/ 505 00
MB-Approval 229.31/229.51
All Porsche vehicles except Cayenne V6

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration

of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

The British Petroleum Company p.l.c. or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local BP office.

Typical Characteristics

Test Methods**Units****Grade :****SAE 0W-40**

<i>Test</i>	<i>Method(s)</i>	<i>Unit</i>	<i>Typical</i>
Density @ 15C, Relative	ASTM D4052	g/ml	0.838
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	12.8
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	75.7
Viscosity, CCS -35C (0W)	ASTM D5293	cP	5850
Flash Point, PMCC	ASTM D93	°C	244
Ash, Sulphated	ASTM D874	% wt	0.7
Total Base Number, TBN	ASTM D2896	mg KOH/g	6.4

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

Lubricants UK Limited
Wakefield House
Pipers Way
Swindon
Wiltshire SN3 1RE
United Kingdom

Telephone +44 (0) 1793 512712
Fax +44 (0) 1793 453983
Technical Helpline +44 (0) 8457 660334
18/05/2010

Date Created: 03/01/2008 15:30:01 Last Modified: 18/05/2010